

ANTI FREEZE 100%



ATOG Antifreeze is a high-performance concentrated antifreeze formula that needs to be diluted before use.

Applications :

Antifreeze 100 percent is recommended for use in applications requiring BS6580 – 1992 quality standard. Antifreeze must be diluted with water before use. It is hard water-compatible and it can be mixed with tap water before filling into the cooling system

Water Specifications	
Hardness, °dGH (mmol/l)	0 – 20 (0 – 3.6)
Chloride Content, ppm max	100
Sulphate Content, ppm max	100

Dilution Table

Antifreeze	Water	Freeze protection
33 %	67 %	-18°C
50 %	50 %	-36°C
60 %	40 %	-52°C

Features and Advantages :

Antifreeze 100 percent holds Mono Ethylene Glycol and avert winter freezing and summer overheating over a 2 years period.

Handling health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding can contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

Specifications :

Antifreeze is recommended for use in applications requiring the following specification:
BS6580-1992

Technical Specifications :

Color	Blue
Density at 20°C, g/cm ³	1.13
Boiling Point, °C	>165
Flash Point, °C	> 115
pH value	7.7
Reserve Alkalinity (M/10HCl), ml	21
Water Content, % max	5